

Top performance for all your laundry needs

The new PERFORMANCE and PERFORMANCE PLUS washing machines offering load capacities from 25 to 45 lbs

THE BENCHMARK MACHINES

High wash performance

Perfect user convenience

Low operating costs

Patented honeycomb drum 2.0 with newly designed shower ribs

OneFingerTouch automatic door lock

New geometry of suds container requires up to 20% less water

Optimum wash rhythm EcoSpeed

Customized wash programs

More efficient heating leads to energy savings of up to 30%

PERFORMANCE

Highlights:

- Convenient OneFingerTouch door closure
- Patented honeycomb drum 2.0
- Improved suds container design



Washing machine	PW 413	PW 418
User interface	Profitronic D	Profitronic D
Load capacity [lb]	30	45
Drum volume [cu. ft.]	4.6	6.4
Max. spin speed [rpm]	1025	950
g-factor/residual moisture [%]*	360/50	360/50
Cycle time** [mins.]	52	52
Heating type	Electric, Non-heated	Electric, Non-heated
Standard voltage	3 AC 220-240V 60 Hz (convertible to 3 AC 200-208V 60 Hz)	3 AC 220-240V 60 Hz (convertible to 3 AC 200-208V 60 Hz)
Rated load [kW]	Electric: 10.2-11.8 (8.8-9.4) Non-heated: 2.3 (2)	Electric: 11.9-13.6 (10.4-11.0) Non-heated: 3 (3)
Fuse rating	Electric: 3-pole 25 A Non-heated: 3-pole 16 A	Electric: 3-pole 40 A Non-heated: 3-pole 16 A
Drainage [NPS 2 3/4", DN 70]	Dump valve	Dump valve
Front color	Octoblué	Octoblué
External dimensions H/W/D [in]	53.3 / 31.5 / 39.8	57.2 / 36.4 / 37.4

PERFORMANCE-PLUS

Highlights

- Freely programmable controls
- EcoSpeed optimum wash rhythm
- Convenient OneFingerTouch door closure
- Patented honeycomb drum 2.0
- Improved suds container design



Washing machine	PW 811	PW 814	PW 818
User interface	Profitronic M	Profitronic M	Profitronic M
Load capacity [lb]	25	35	45
Drum volume [cu. ft.]	3.9	5.0	6.4
Max. spin speed [rpm]	1150	1075	1075
g-factor/residual moisture [%]*	460/45	460/45	460/45
Cycle time** [mins.]	45	45	45
Heating types	Electric	Electric, Steam	Electric, Steam
Standard voltage	3 AC 220-240V 60 Hz (convertible to 3 AC 200-208V 60 Hz)	3 AC 220-240V 60 Hz (convertible to 3 AC 200-208V 60 Hz)	3 AC 220-240V 60 Hz (convertible to 3 AC 200-208V 60 Hz)
Rated load [kW]	Electric: 10.2-11.8 (8.8-9.4)	Electric: 14.8-17.1 (12.5-13.4) Steam: 2.3 (2.3)	Electric: 19.4-22.6 (16.6-17.7) Steam: 3 (3)
Fuse rating	Electric: 3-pole 25 A	Electric: 3-pole 40 A Steam: 3-pole 16 A	Electric: 3-pole 50 A Steam: 3-pole 16 A
Drainage [NPS 2 3/4", DN 70]	Dump valve	Dump valve	Dump valve
Front color	Stainless steel	Stainless steel	Stainless steel
External dimensions H/W/D [in]	53.3 / 31.5 / 37.0	57.2 / 36.4 / 33.5	57.2 / 36.4 / 37.4

* Residual moisture after hot final rinse ** Cycle time for Cottons program 140°F, hot water fill, 3N AC 400V 50Hz