

## EXSM Series 220-300G Solid Mount Washers

Wascomat's 65, 80, and 135 lb. capacity EXSM solid mount washers are designed for large, family-sized loads. Higher G-force means less drying time, so you'll save big on energy costs. Self-service laundries benefit from a faster throughput — freeing up dryers, folding tables and parking spots — which increases store profits. Your customers will appreciate the fast and superior results!



**Wascomat EXSM Series Washers with Compass Pro** continue a long tradition of excellence in technology, design, and quality:

- AS (Automatic Savings) - Save up to 50% on water with AS, automatically. With every wash cycle, AS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs
- Heavy-duty construction for demanding environments and large family-sized loads
- Low water consumption
- Efficient frequency-controlled motor reduces peak power demand by 50% for energy savings
- Soft-grip, slip-lock door handle for safe and trouble-free operation
- Large door opening for easy loading and unloading
- Unique 4-compartment supply dispenser lets the customer conveniently load all laundry supplies before starting the wash
- Easily create custom wash programs

### Features and Benefits

Wascomat Compass Pro provides the ultimate in flexibility:

- Customize wash programs to lower costs and meet customer demands
- Create fully customized programs for your specific market
- Heavy Soil and Extra Rinse options increase store revenue and boost customer satisfaction
- Display wash program information in two languages simultaneously
- Value Pricing — set different prices for different wash programs and option keys
- Real-time clock for happy hour, promotional pricing
- **NOTE:** The 135 lb washer does NOT have AS

### 220-300 G-Force Extraction

The perfect balance of speed, performance, and BIG savings. High-speed spin removes more water for faster drying times and better wash performance.

### Compass Pro Microprocessor

With Compass Pro you choose the programs that best suit your needs. Modify standard wash programs to find the perfect balance between low water and energy consumption — or create your own programs to meet the specific needs of your market. Displays two languages at the same time.

Easily program a higher price for hot wash, extra rinse, and heavy soil. Program discount prices for slow periods of the day or week.

**Compass Pro puts you  
in complete control of  
your laundry business.  
One knob does it all!**

Wascomat EXSM Series, 220-300G Washers	EXSM765		EXSM780		EXSM 7135	
Capacity (lb/kg)	65	30	80	36	135	60
Width (in/mm)	36 3/4	933	43 7/8	1115	46 3/16	1173
Depth (overall) (in/mm)	38 3/4	985	44 1/8	1121	50 5/8	1286
Height (in/mm)	57 5/16	1456	61 13/16	1570	65 7/8	1673
Height to bottom of door (in/mm)	20 1/2	520	21	534	21 1/4	540
Door opening diameter (in/mm)	16 1/8	410	21 1/16	535	21 1/16	535
Cylinder volume (ft <sup>3</sup> /l)	9.9	280	12.4	350	21.2	600
Drain outlet diameter (in/mm)	2 15/16	75	2 15/16	75	2 15/16	75
Height to centerline of drain (in/mm)	4 11/16	119	4 13/16	122	4 1/16	103
Extract (rpm/G-Force)	805 / 300		650 / 220		630 / 220	
Dynamic floor load (lb/kN)	1101 +/- 2135	4.9 +/- 9.5	1551 +/- 2405	6.9 +/- 10.7	2248 +/- 3507	10 +/- 15.6
Dynamic frequency (Hz)	13.4		10.8		10.5	
Noise level (dBA) in extraction	<75		<82		<84	
Crated width - (in/mm)	43 5/16	1100	44 7/8	1140	47 5/8	1210
Crated depth - (in/mm)	45 11/16	1160	54 5/16	1380	55 1/8	1400
Crated height - (in/mm)	62 5/8	1590	67 11/16	1720	72 13/16	1850
Crated weight (lb/kg)	882	401	1272	579	1920	873
<b>Electrical Requirements (standard)</b>						
Voltage/frequency/phase	208-240/60/1 or 3-		208-240/60/1 or 3-		208-240/60/3-	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 7.2 / 15		1.8 / 8.6 / 15		2.6 / 7.2 / 15	
Voltage/frequency/phase	480 / 60 / 1 or 3-		480/60/1 or 3-		480/60/3-	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 3.1 / 10		1.8 / 3.8 / 10		2.6 / 3.1 / 10	
<b>Water Information</b>						
Inlet fittings (* = 3 inlets)	3/4"	DN20	3/4"	DN20	1"	DN25
Flow (gpm/lpm @ 45 psi) (each inlet)	16	60	16	60	25	110
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	n/a					
Modified Energy Factor						
Water Factor (Gal per cycle/drum volume)						
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.						



\* **NOTE:** The 135 lb washer does NOT have AS.



**Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.**



**Laundrylux**

**800.645.2204 • laundrylux.com**

Laundrylux • 461 Dougherty Blvd., Inwood, NY 11096-0338

**Sales & Administration:** 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

**Parts:** 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

**Tech Support:** 516-371-0700 • F 516-371-4029 • service@laundrylux.com

**En Mexico:** Llame gratis a este numero 001-800-010-1010